TECHNICAL SPECIFICATIONS

motor electric 9 kW at 3500 r.p.m. (72V)

position rear transversal

type asinchronous AC, with electronic motor controller

80 Nm at 0 r.p.m.

torque alternating current power supply LiFePO₄14,6 kWh

batteries IES ELIPS 3300 on board

charger driver axle and electric change direction

transmission 8,89 gearbox rack

steering double independent circuit (front-rear)

brakes front and Rear discs Ø238 mm

front: Overlapping triangles with combined spring and shock absorbers

suspension (front/rear) rear: Levers pulled with torque limiter combined with shock-absorber

and spiring

165/70 R13C 88/86R

tires 55 km/h up to 120 km


autonomy

DIMENSIONS AND VOLUMES


length	3370 mm
width	1200 mm
height	1805 mm
wheelbase	1735 mm
track width	1035 mm
cargo length (pickup)	2100x1200 mm
volume charge (cargo box)	3000 litres

MASAS

technically permissible	1510 Kg
maximum laden mass	
mass of the vehicle in	929 Kg
running order	
payload	581 Kg







Distributor Stamp:

T-Truck_{N1}





homologated N1 to drive on public roads
LiFePO₄ batteries of 14,6 kWh
asinchronous motor 9 kW
up to 120 km of autonomy






New Version TTRUCK N1 for goods transport

It offers a wide range of options and implements for any type of work. Furthermore it is possible to implement the best solution for your work.



Closed cargo box in fiber with volume of 3000 litres capacity







Rear bed fixed with 3 doors in aluminium and height extension in grating Dimensions: 2100x1200x365 + 710 mm

The combination of asinchronous motors AC and 72V power, along with high-performance batteries Lithium-Iron-Posfato (LiFePO $_{\Delta}$), with 14.6 kWh, give easy handling, high agility and mobility. They are excellent vehicles for use in urban and peripheral cores.

The cabin is built with an important ergonomic study for everyday use.

FEATURES

Rugged steel chassis, Anti-oxide treatment by cataphoresis, Aluminum cabin, ergonomic seats, onboard charger, TRW brake system, Electronic power controller, AC motor 9 kW, LiFePO₄ Batteries 14.6 Kwh

OPTIONS

- 1 rear view camera
- 3 trailer hitch
- 5 heater system webasto
- 2 rack roof
- 4 radio cd/mp3
- 6 rotating light











COLORS

Serie







