



L7 APPROVED

OPTIONS



Radio USB



Heater system



Rotating light



Tool box



Open cargo box aluminium; Opt. Grating



Closed cargo box in fiber

COLORS

White



Custom



TECHNICAL SPECIFICATIONS

Motor :	Electric 8 kW(L7e) - 48V. · 9 kW(L7e) - 72V.
Position :	Rear transversal.
Type :	Asynchronous electric AC motor with electronic power controller.
Power (kW CEE):	8 kW @ 4500 rpm. - 48V. · 9kW @ 3.500 rpm. - 72V.
Torque (Nm) :	60 at 0 rpm.60 Nm at 0 rpm. - 48V. - 80 Nm at 0 rpm. -72V.
Battery :	9,6 kWh Lithium batteries (LiFePO4) 48V. (4,5h. full charge). 14,6 kWh Lithium batteries (LiFePO4) 72V. (6h. full charge).
TPMLM:	1460Kg.
Payload:	557Kg. - 48V. · 512kg. - 72V.
Charger :	Alim. 220V AC 16A 2200W.
Transmission :	Driver axle and electric gearshift.
Steering :	Rack & pinion.
Brake :	Double independent circuit (front-rear) Front and Rear Disc. Ø 238mm. Mechanical parking brake on rear axle.
Suspension :	Overlapping Triangles with combined spring and shock absorbers. Levers pulled with torque limiter combined with shock-absorber and spring
Tyre :	Front and Rear 165/70R13
Maximum speed :	50 km/h.
Range* :	80 km (depending on temperature, weight, shape, grade, surface and driving conditions. Consult us).

T-Truck+
COMARTH

